



# ISTITUTO GIORDANO

EC NOTIFIED BODY No. 0407

## EC CERTIFICATE OF FACTORY PRODUCTION CONTROL

**0407-CPD-563 (IG-170-2012)**

In compliance with the Council Directive 89/106/EEC of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products (the Construction Products Directive or CPD), as amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

### METAL CHIMNEYS

identified as shown overleaf (Annex)

produced by the manufacturer

#### FIG S.L.

**Pol. Ind. El Boreo, Nave 16B Y 17 50172 ALFAJARIN (ZARAGOZA) - Espana**

In the factory

**Pol. Ind. El Boreo, Nave 16B Y 17 50172 ALFAJARIN (ZARAGOZA) - Espana**

is submitted by the manufacturer to the initial type-testing of the product, a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body Istituto Giordano S.p.A. has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standards

### EN 1856-2:2009

were applied.

This certificate was first issued on 06/08/2012 and remains valid as long as the conditions laid down in the technical specification in reference or the manufacturing conditions in the factory or the factory production control itself are not modified significantly.

Bellaria-Igea Marina - Italia, 06/08/2012

Revision No. 0



CPD Technical Director

Dott. Ing. Giuseppe Persano Adarno

Managing Director

Dott. Ing. Vincenzo Iommi

Page 1 of 2

**ANNEX TO CERTIFICATE  
0407-CPD-563 (IG-170-2012)**

Revision No. 0 dated 06/08/2012

PRODUCT IDENTIFICATION	TYPE	DESIGNATION
TUBO ALUEXTRA Aluminium connecting flue pipe (EN AW - 6060) with a thickness of 1 mm.  Diameters range: 80 ÷ 130 mm	with gaskets	Connecting flue pipe EN 1856-2 T190-P1-W-Vm L13100-O(150)M

